

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4033

Safety data sheet no.: 49PM20345

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

email: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number: Telefon: +49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS05

Signal word Danger**Hazard-determining components of labelling:**

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P362 Take off contaminated clothing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Siliciumdioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 1317-65-3 EINECS: 215-279-6	limestone substance with a Community workplace exposure limit	25-50%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO ₄ x n H ₂ O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	5-10%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	5-10%
CAS: 68475-76-3 EINECS: 270-659-9 Reg.nr.: 01-2119486767-17-xxxx	Flue dust, portland cement ☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	0.1-1%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 2)

After inhalation Supply fresh air; consult doctor in case of complaints.**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

Information for doctor None**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents**

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters**Protective equipment:** Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid formation of dust.

Ensure adequate ventilation.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.**6.3 Methods and material for containment and cleaning up:** Pick up mechanically.**6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

(Contd. on page 4)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 3)

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****DNELs****CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)**

Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	5.29 mg/m ³ (consumer long term value) 21.17 mg/m ³ (worker systemic long term value) 5,082 mg/m ³ (worker systemic short term value) 3,811 mg/m ³ (consumer systemic short term value)

CAS No.	Designation of material	%	Type	Value	Unit
---------	-------------------------	---	------	-------	------

CAS: 14808-60-7 Siliciumdioxide (Quartz sand)

BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction				
MAK (Germany)	alveolengängige Fraktion				
GV (Denmark)	Long-term value: 0.3* 0.1** mg/m ³ *total; **total, respirabel, K				
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y				
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2 (r)				
VLE (Portugal)	Long-term value: 0.025 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão				
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion				
HTP (Finland)	Long-term value: 0.05 mg/m ³ alveolijae				

CAS: 1317-65-3 limestone

TWA (Italy)	Long-term value: 10 mg/m ³ (e)
-------------	--

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 4)

CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
AGW (Germany)	Long-term value: 6 A mg/m ³ DFG
LEP (Spain)	Long-term value: 10 mg/m ³ e
TWA (Italy)	Long-term value: 10 mg/m ³ (i)
VLE (Portugal)	Long-term value: 10 mg/m ³ Fração inalável; Sintomas nasais
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä/inhalerbart, **alveolijae/respirabel

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Recommended thickness of the material: ≥ 0.15 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name **weber.floor 4033**

(Contd. of page 5)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles**Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Powder
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C:	> 12.0 (DIN 19261) In water
---------------------------	--------------------------------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point:	Not applicable
---------------------	----------------

Flammability (solid, gas):	Product is not flammable.
-----------------------------------	---------------------------

Ignition temperature:	Not determined.
------------------------------	-----------------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Auto-ignition temperature:	Product is not selfigniting.
-----------------------------------	------------------------------

Explosive properties:	Product does not present an explosion hazard.
------------------------------	---

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Oxidising properties	Not determined.
-----------------------------	-----------------

Vapour pressure:	Not applicable.
-------------------------	-----------------

Density:	Not applicable.
-----------------	-----------------

Bulk density:	Not determined.
----------------------	-----------------

Vapour density	Not applicable.
-----------------------	-----------------

Evaporation rate	Not applicable.
-------------------------	-----------------

Solubility in / Miscibility with Water at 20 °C:	1.5 g/l
---	---------

Segregation coefficient (n-octanol/water) log Pow:	Not determined.
---	-----------------

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 6)

Viscosity:
dynamic: Not applicable.
kinematic: Not applicable.
Solvent content:
Organic solvents: 0.0 %
EU-VOC (%) 0.00 %
EU-VOC (g/L) 0.0 g/l
Solids content: 100 %
9.2 Other information None.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / Conditions to be avoided:
No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions
Reacts with light alloys in the presence of moisture to form hydrogen
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.
LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 1317-65-3 limestone			
Oral	LD50	>5,000 mg/kg	(Rat)
CAS: 65997-16-2 Cement, alumina, chemicals			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO4 x n H2O (n = 0; 1/2; 2)			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

Primary irritant effect:
Skin corrosion/irritation
Causes skin irritation.
Serious eye damage/irritation
Causes serious eye damage.
Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.
Carcinogenicity Based on available data, the classification criteria are not met.
Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 7)

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
CAS: 1317-65-3 limestone			
LC50/96h	>10,000 mg/l	(Oncorhynchus mykiss (Rainbow trout))	
EC50/48h	>1,000 mg/l	(Daphnia magna)	
EC50/72h	>200 mg/l	(Algae)	
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)			
LC50/48h	>79 mg/l	(Daphnia magna)	
LC50/96h	>79 mg/l	(Oryzias latipes (Japanese medaka))	
EC50/24h	>790 mg/l	(Activated sludge)	
EC50/72h	>79 mg/l	(Selenastrum capricornutum (Green algae))	

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

The product contains substances which causes severe clouding in water

Remark: The product causes a significant pH change. Neutralise before introduction.

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

Possible waste code 17 09 04.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 8)

10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge

Uncleaned packaging:
Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.
Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 47

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

EUG

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.01.2020

Version number 2

Revision: 03.01.2020

Trade name weber.floor 4033

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Department issuing SDS: Product safety department.

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.