

weber.floor 4965

Parking strips

Self-adhesive foam strips for masking fixtures, drains and for limitation of working sections

Fields of application

For limitation of working sections during floor levelling works in residential, commercial and industrial buildings. For masking fixtures and drains.

Description

weber.floor 4965 is a factory-made foam strip.

Main features

- self-adhesive
- simple and fast processing
- height 15 mm, width 15 mm, length 2 m
- high bonding strength

Quality control

weber.floor 4965 is subject to a regular quality control by self-monitoring.

Substrates

- All clean substrates are allowed.

Substrate preparation

- The substrate must be load-bearing, clean, dry, free of laitance, oil, grease, dust and free of all adhesion-impairing substances.

Working instructions

- When smoothing mortars and levelling compounds are pumped, limited working sections must be determined, in order to ensure the full workability of the product (mixing, levelling and smoothing) within its pot life. Therefore, the width of each working section should not exceed a certain width, so that the material can flow together within the same section.
- If the specified width is exceeded, use the self-bonding foam strip weber.floor 4965 in order to form bays and stop ends.

Practical information

Storage:

The product can be stored for up to 5 years, if kept dry and cool.

Packagings

Type	Sales unit	Number / euro-pallet
Rod	2 running meters	25 pieces