

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4515

Safety data sheet no.: 49PM20367

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84 D-40549 Düsseldorf +49(0)211/91369-0

email: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number: Telefon: +49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Flue dust, portland cement

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

(Contd. of page 1)

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362 Take off contaminated clothing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Does not contain PBT substances. vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Ready-mixed mortar with Portland cement

Dangerous components:		
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 %	50-75%
CAS: 1317-65-3 EINECS: 215-279-6	Eye Dam. 1; H318: C ≥ 1 % limestone substance with a Community workplace exposure limit	10-20%
CAS: 93763-70-3 EC number: 618-970-4	Perlite substance with a Community workplace exposure limit	5-10%
CAS: 68475-76-3 EINECS: 270-659-9 Reg.nr.: 01-2119486767-17- xxxx	Flue dust, portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	1-2%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

After swallowing

(Contd. of page 2)

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Information for doctor None

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Avoid formation of dust.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

(Contd. of page 3)

Ingredients with limit values that require monitoring at the workplace:

CAS No. Design	CAS No. Designation of material % Type Value Unit		
CAS: 65997-15-1	CAS: 65997-15-1 cement portland, grey		
AGW (Germany)	Long-term value: 5 E mg/m³ DFG		
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d		
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4		
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma		
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae		
CAS: 1317-65-3	imestone		
TWA (Italy)	Long-term value: 10 mg/m³ (e)		
CAS: 93763-70-3	3 Perlite		
LEP (Spain)	Long-term value: 10 mg/m³ e		
TWA (Italy)	Long-term value: (10) mg/m³ (A4 (e))		
VLE (Portugal)	Long-term value: 10 mg/m³ A4; Irritacao		

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Protection of hands:

Protective gloves.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Recommended thickness of the material: ≥ 0.15 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

(Contd. of page 4)

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level ≤ 6 The exact breaktrough time has to be found out by the manufacturer of the protective gloves and

has to be observed.

Eye protection: Tightly sealed goggles **Body protection:** Protective work clothing.

SECTION 9: Phy	ysical and c	hemical	properties
----------------	--------------	---------	------------

9.1 Information on basic physical and cher General Information	nical properties
Appearance: Form: Colour: Odour: Odour threshold:	Powder According to product specification Characteristic Not determined.
pH-value at 20 °C:	> 12.0 (DIN 19261) In water
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.
Flash point:	Not applicable
Flammability (solid, gas):	Product is not flammable.
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper: Oxidising properties	Not determined. Not determined. Not determined.
Vapour pressure:	Not applicable.
Density:	Not applicable.
Bulk density: Vapour density Evaporation rate	Not determined. Not applicable. Not applicable.
Solubility in / Miscibility with Water at 20 °C:	1.5 g/l
Segregation coefficient (n-octanol/water) lo	og Not determined.
Viscosity: dynamic: kinematic: Solvent content:	Not applicable. Not applicable.
Organic solvents:	0.0 %



according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

		(Contd. of page 5)
EU-VOC (%)	0.00 %	
EU-VOC (g/L)	0.0 g/l	
Solids content:	100.0 %	
9.2 Other information	None.	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	Туре	Value	Species	
CAS: 6	5997-1	5-1 cement portland, grey	/		
Dermal	LD50	>2,000 mg/kg (Rabbit)			
CAS: 13	317-65	-3 limestone			
Oral	LD50	>5,000 mg/kg (Rat)			

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

(Contd. on page 7)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

(Contd. of page 6)

Type of test Effective concentration Method Assessment CAS: 1317-65-3 limestone LC50/96h | >10,000 mg/l (Oncorhynchus mykiss (Rainbow trout)) EC50/48h | >1,000 mg/l (Daphnia magna) EC50/72h | >200 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark:

The product contains substances which causes severe clouding in water

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Remark: The product causes a significant pH change. Neutralise before introduction.

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10	
10 13 14	waste concrete and concrete sludge	1

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled

after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

SECT	ION 14:	Transport	informat	ion

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Version number 1 Revision: 05.02.2021

Trade name weber.floor 4515

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Ann of Marpol and the IBC Code	nex II Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eve damage.

H335 May cause respiratory irritation.

Department issuing SDS: Product safety department.

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

(Contd. of page 8)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.02.2021 Revision: 05.02.2021 Version number 1

Trade name weber.floor 4515

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation) vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.