

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **weber.floor 4715 Komp.A**

Safety data sheet no.: 49PX20377-a

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

email: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number: Telefon: +49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Reaction resin based on bisphenol-A

Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	2, 2' - [(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	>50%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	10-20%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 2)

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

EUG

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from freezing.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Oral	Derived No Effect Level	0.75 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8.33 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	3.571 mg/kgxday (consumer systemic long term value)
		12.25 mg/m ³ (worker systemic long term value)

CAS: 100-51-6 Benzyl alcohol

Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
		22 mg/m ³ (worker systemic long term value)
		5.4 mg/m ³ (consumer systemic long term value)

CAS No.	Designation of material	%	Type	Value	Unit
---------	-------------------------	---	------	-------	------

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

MAK (Germany)	vgl. Abschn. IIb
---------------	------------------

CAS: 100-51-6 Benzyl alcohol

AGW (Germany)	Long-term value: 22 mg/m ³ , 5 ppm 2(I);DFG, H, Y, 11
HTP (Finland)	Long-term value: 45 mg/m ³ , 10 ppm

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 4)

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.
In case of brief exposure or low pollution use respiratory filter device.
In case of intensive or longer exposure use self-contained respiratory protective device.
Short term filter device:

Filter A2

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: \geq (Butyl) 0.7mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level \leq 6

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value:	Not applicable.
------------------	-----------------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 5)

Flash point:	> 100 °C (DIN ISO 2592)
Ignition temperature:	435 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	1.3 Vol. %
Upper:	13.0 Vol. %
Oxidising properties	Not determined.
Vapour pressure at 20 °C:	0.1 hPa
Density at 20 °C:	1.14 g/cm ³ (DIN EN ISO 2811-2)
Bulk density:	Not applicable.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic at 20 °C:	800-900 mPas (DIN EN ISO 3219)
kinematic:	Not determined.
	Not determined.
Solvent separation test:	Not determined
Solvent content:	
EU-VOC (%)	12.50 %
9.2 Other information	None.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with alcohols, amines, aqueous acids and alkalis

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Irritant gases/vapours

-EUG-

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			
Oral	LD50	15,000 mg/kg (Rat)	
Dermal	LD50	23,000 mg/kg (Rat)	
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,230 mg/kg (Rat)	
Dermal	LD50	2,000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE) >4,178 mg/l (Rat)	

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Type of test	Effective concentration	Method	Assessment
CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane			
IC50/72h	1.7-1.8 mg/l	(Fish)	
LC50/96h	1.2-3.6 mg/l	(Fish)	
EC50/48h	1.1-2.8 mg/l	(Daphnia magna)	
EC50/72h	9.4-11 mg/l	(Algae)	
NOEC (21d)	0.3 mg/l	(Daphnia magna)	
CAS: 100-51-6 Benzyl alcohol			
LC50/48h	360 mg/l	(Daphnia magna)	
	645 mg/l	(Leuciscus idus (Orfe))	
LC50/96h	10 mg/l	(Lepomis macrochirus (Sunfish))	

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 7)

EC50/24h	460 mg/l (Pimephales promelas (Minnow))
EC50/96h	400 mg/l (Daphnia magna)
	640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential

CAS: 100-51-6 Benzyl alcohol

EBAB | 1.1 log Pow (Bioaccumulation)

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark:

The product contains substances which are toxic to fishes and bacteria.

Toxic for fish

Behaviour in sewage processing plants:

Type of test Effective concentration Method Assessment

CAS: 100-51-6 Benzyl alcohol

EC 50 (3h) | 79 mg/l (Scenedesmus quadricauda (Algae))

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Curing of the product by mixing with the curing component. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 8)

Uncleaned packaging:
Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name
ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

14.3 Transport hazard class(es)
ADR

Class

9 (M6) Miscellaneous dangerous substances and articles.

Label

9

IMDG, IATA

Class

9 Miscellaneous dangerous substances and articles.

Label

9

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:
Marine pollutant:

Yes

Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.

Hazard identification number (Kemler code):

90

EMS Number:

F-A,S-F

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 9)

Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	-
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.06.2020

Version number 4

Revision: 08.06.2020

Trade name weber.floor 4715 Komp.A

(Contd. of page 10)

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Product safety department.**Contact:** Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.