

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4715 Komp.B

Safety data sheet no.: 49PX20377-b

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

email: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number: Telefon: +49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361f Suspected of damaging fertility.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EUG

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 1)

Hazard pictograms


GHS05 GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

4-tert-butylphenol
 m-phenylenebis(methylamine)
 3,3,5-trimethylhexamethylene-diamine

Hazard statements

H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H361f Suspected of damaging fertility.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapours.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 01-2119489419-21-xxxx	4-tert-butylphenol ⚠ Repr. 2, H361f; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315	10-25%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	5-10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 2)

 CAS: 25620-58-0
 EINECS: 247-134-8

 3,3,5-trimethylhexamethylene-diamine
 ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin
 Sens. 1, H317; Aquatic Chronic 3, H412

5-10%

SVHC

CAS: 98-54-4 | 4-tert-butylphenol

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents

 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from freezing.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 98-54-4 4-tert-butylphenol		
Oral	Derived No Effect Level	0.026 mg/kgxday (consumer systemic long term value)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 4)

Dermal	Derived No Effect Level	0.071 mg/kgxday (worker systemic long term value) 0.026 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	0.5 mg/m ³ (worker systemic long term value) 0.09 mg/m ³ (consumer systemic long term value)
CAS: 1477-55-0 m-phenylenebis(methylamine)		
Dermal	Derived No Effect Level	0.33 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	1.2 mg/m ³ (worker systemic long term value) 0.2 mg/m ³ (worker local long term value)
CAS: 100-51-6 Benzyl alcohol		
Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value) 4 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	22 mg/m ³ (worker systemic long term value) 5.4 mg/m ³ (consumer systemic long term value)

Ingredients with biological limit values:**CAS: 98-54-4 4-tert-butylphenol**

BGW (Germany)	2 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 4-tert-Butylphenol (p-tert-Butylphenol) (nach Hydrolyse)
---------------	--

CAS No.	Designation of material	%	Type	Value	Unit
---------	-------------------------	---	------	-------	------

CAS: 98-54-4 4-tert-butylphenol

AGW (Germany)	Long-term value: 0.5 mg/m ³ , 0.08 ppm 2(II);DFG, H, 11
GV (Denmark)	Long-term value: 0.5 mg/m ³ , 0.08 ppm H
LEP (Spain)	Short-term value: 1* mg/m ³ , 0.16* ppm Long-term value: 0.5* mg/m ³ , 0.08* ppm *Propuesta de modificación: vía dérmica, Sen, ae

CAS: 1477-55-0 m-phenylenebis(methylamine)

MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IV
GV (Denmark)	Ceiling limit: 0.1 mg/m ³ , 0.02 ppm LH
TWA (Italy)	Ceiling limit: 0.1 mg/m ³ Cute
VLE (Portugal)	Ceiling limit: 0.1 mg/m ³ P; Irritação ocular, cutânea e GI
HTP (Finland)	Ceiling limit: 0.1 mg/m ³ iho

CAS: 100-51-6 Benzyl alcohol

AGW (Germany)	Long-term value: 22 mg/m ³ , 5 ppm 2(I);DFG, H, Y, 11
HTP (Finland)	Long-term value: 45 mg/m ³ , 10 ppm

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 5)

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A2

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Yellowish
Odour:	Amine-like
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 6)

Initial boiling point and boiling range:	Undetermined.
Flash point:	> 100 °C (DIN ISO 2592)
Ignition temperature:	365 ° C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	1.3 Vol.% (DIN 51649)
Upper:	13.0 Vol. % (DIN 51649)
Oxidising properties	Not determined.
Vapour pressure:	0.1 hPa (DIN 51640)
Density at 20 °C:	1.03 g/cm ³ (DIN EN ISO 2811-2)
Bulk density:	Not applicable.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic at 20 °C:	400 mPas (DIN EN ISO 3219)
kinematic:	Not determined.
Solvent separation test:	Not determined
9.2 Other information	None.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidizing agents

Exothermic polymerisation.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Irritant gases/vapours

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

EUG

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 7)

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 98-54-4 4-tert-butylphenol			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 1477-55-0 m-phenylenebis(methylamine)			
Oral	LD50	2,000 mg/kg	(Rat)
Dermal	LD50	>3,100 mg/kg	(Rabbit)
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,230 mg/kg	(Rat)
Dermal	LD50	2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	11 mg/l	(ATE)
		>4,178 mg/l	(Rat)
CAS: 25620-58-0 3,3,5-trimethylhexamethylene-diamine			
Oral	LD50	910 mg/kg	(Rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity**

Suspected of damaging fertility.

STOT-single exposure Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:** No further relevant information available.

Type of test	Effective concentration	Method	Assessment
CAS: 98-54-4 4-tert-butylphenol			
EC50/48h	3.9 mg/l	(Daphnia magna)	
EC50/72h	14 mg/l	(Selenastrum capricornutum (Green algae))	
NOEC (21d)	0.73 mg/l	(Daphnia magna)	
CAS: 1477-55-0 m-phenylenebis(methylamine)			
LC50/96h	87.6 mg/l	(Oryzias latipes (Japanese medaka))	
EC50/48h	15.2 mg/l	(Daphnia magna)	
EC50/72h	20.3 mg/l	(Scenedesmus subspicatus (Algae))	

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 8)

CAS: 100-51-6 Benzyl alcohol

LC50/48h	360 mg/l (Daphnia magna) 645 mg/l (Leuciscus idus (Orfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sunfish)) 460 mg/l (Pimephales promelas (Minnow))
EC50/24h	400 mg/l (Daphnia magna)
EC50/96h	400 mg/l (Daphnia magna) 640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

CAS: 25620-58-0 3,3,5-trimethylhexamethylene-diamine

LC50/48h	174 mg/l (Leuciscus idus (Orfe))
LC0/96h	150 mg/l (Leuciscus idus (Orfe))
EC50/24h	31.5 mg/l (Daphnia magna)
EC50/72h	29.5 mg/l (Scenedesmus subspicatus (Algae))
EC 10	72 mg/l (Pseudomonas putida (Bacteria))

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential
CAS: 100-51-6 Benzyl alcohol

EBAB	1.1 log Pow (Bioaccumulation)
------	-------------------------------

Behaviour in environmental systems:
12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:
Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

The product contains substances which are toxic to fishes and bacteria.

Harmful to fish

Behaviour in sewage processing plants:
Type of test Effective concentration Method Assessment
CAS: 100-51-6 Benzyl alcohol

EC 50 (3h)	79 mg/l (Scenedesmus quadricauda (Algae))
------------	---

Additional ecological information:
General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

(Contd. on page 10)

EUG

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

12.6 Other adverse effects No further relevant information available.

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After mixing with the resin component pour a partial amount back into the curing agent barrel, stir well and pour the mass back once more. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP6	Acute Toxicity
HP8	Corrosive
HP10	Toxic for reproduction
HP13	Sensitising
HP14	Ecotoxic

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN2735

14.2 UN proper shipping name
ADR

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 4-tert-butylphenol), ENVIRONMENTALLY HAZARDOUS

IMDG

AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 4-tert-butylphenol), MARINE POLLUTANT

IATA

AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 4-tert-butylphenol)

14.3 Transport hazard class(es)

ADR



Class

8 (C7) Corrosive substances.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 10)

Label	8
IMDG	
	
Class	8 Corrosive substances.
Label	8
IATA	
	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substances: 4-tert-butylphenol
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80
EMS Number:	F-A,S-B
Segregation groups	Alkalis
Stowage Category	A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), 4-TERT-

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 11)

BUTYLPHENOL), 8, II, ENVIRONMENTALLY
HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category E2** Hazardous to the Aquatic Environment**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**National regulations****Other regulations, limitations and prohibitive regulations****Medical check-ups**

CAS: 98-54-4 | 4-tert-butylphenol

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Product safety department.**Contact:** Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.08.2019

Version number 3

Revision: 01.08.2019

Trade name weber.floor 4715 Komp.B

(Contd. of page 12)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG