

weber.tec 974

Primer

Solvent-containing primer for non-absorbent substrates with polysulfide joint sealants

Fields of application

As solvent-based primer for the polyurethane joint sealants weber.tec 970 and weber.tec 971 on non-absorbent substrates.

Description

weber.tec 974 is a 1-component solvent-based primer based on silane.

Composition

Silane base, solvent

Main features

- good workability
- very good bonding strength
- solvent-containing
- good workability

Technical values

Density:	approx. 0.8 kg/dm ³
Drying time:	approx. 10 - 15 minutes (at +23°C)

Quality control

weber.tec 974 is subject to a regular quality control.

General notes

- Do not add any foreign substances during application.

Substrate preparation

- The substrate must be dry, solid, load-bearing, rough, clean and free from all adhesion-impairing particles and substances.
- The substrate preparation must be adapted to the specific job site conditions.

Working instructions

- Apply weber.tec 974 in a uniform coat, using a paintbrush.
- The joint sealants weber.tec 970 or tec 971 can be applied after 10 - 15 minutes (at +23°C) at the earliest, but after 4 hours at the latest.

Practical information

Drying time:
at least 10 - 15 minutes

Tools:
Paintbrush

Storage:
The product can be stored at least 12 months in its original unopened packaging, if kept dry and frost-free.

Consumption / yield

depending on substrate roughness: approx. 10 - 20 ml/m

Packagings

Type	Sales unit	Number / euro-pallet
Metal can	1 liter	4 pieces/cardboard

The information in this technical data sheet is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.