

weber.tec 828 SZ

Cut protection tape

Pre-cut protection insert on sealing tapes

Fields of application

As protection tape for the safe and long-term protection of composite waterproofing in areas of connection and movement joints.

The rust-free and extremely thin stainless steel tape prevents the waterproofing layer from being accidentally cut or damaged with a cutter knife when cutting out and renewing elastic silicone joint sealants.

This measure can be carried out with all **Weber** bonded waterproofing systems: **weber.tec 822** (liquid waterproofing foil) / **824** (1-comp. flexible cement-based waterproofing slurry) / **827** and **827 S** (flexible waterproofing epoxy resins) / **Superflex D 2** (2-comp. reactive waterproofing slurry) and **xerm 844** (2-comp. waterproofing, tile adhesive and de-coupling system).

weber.tec 828 SZ is suitable for use in case of all water load classes W0-I (low load), W1-I (moderate load) and W2-I (high load) according to DIN 18534 "Bonded waterproofing under tiles and slabs with liquid products for interior use". Full information about water loads is given in the technical data sheet of the sealing tape system **weber.tec 828**.

For use indoors and outdoors.

Description

weber.tec 828 SZ is a high-quality stainless steel strip.

Composition

Alloy: 1.4310.4

Main features

- self-bonding
- resistant to chemicals
- extremely thin: 0.24 mm
- high-quality rust-free stainless steel
- easy application
- for use indoors and outdoors

Quality control

weber.tec 828 SZ is subject to a regular quality control.

Working instructions

- Apply the above-mentioned **Weber** bonded waterproofing system according to the working instructions given in the specific technical data sheet.
 - After drying, cut **weber.tec 828 SZ** to the required length, using scissors.
 - Peel off the white paper strip on the reverse side, apply the tape with the self-bonding side directly onto the waterproofed surfaces and press on firmly.
 - The protection tape is correctly fixed when the metal strip is placed exactly at the level of the elastic joint and the orange protective sheathing is facing forward.
-

Practical information

Colour:
silver/orange

Thickness/width:
0.24 mm/20 mm

Storage:
The product can be stored for an unlimited period, if kept dry, protected from moisture and direct sunlight.

Packagings

Type	Sales unit
Roll (paper-covered metal tape, self-bonding)	10 meters

The information in this technical data sheet is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.
