

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

Safety data sheet no.: 49PX20688-b

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating

Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

email: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number: Telefon: +49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1C

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4

H302 Harmful if swallowed.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

GHS07

GHS09

Signal word Danger

Hazard-determining components of labelling:

2-Propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 1)

N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether
 3-aminopropyldiethylamine
 Benzyl alcohol

Hazard statements

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 1173092-74-4 EC number: 630-554-4	2-Propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	>50%
CAS: 84144-79-6 EINECS: 282-199-6 Reg.nr.: 01-2120762088-49-xxxx	N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	25-50%
CAS: 104-78-9 EINECS: 203-236-4 Index number: 612-062-00-1	3-aminopropyldiethylamine ⚠ Flam. Liq. 3, H226; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	2-5%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-2%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

EUG

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

The product must not get into lakes, rivers or canals, the sewage system or into the soil. Dam up or trap any escaping fluid immediately.

The product must not get into watercourses or into the soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

EUG

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.
Provide floor trough without outlet.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

CAS: 100-51-6 Benzyl alcohol

Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value)
		4 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	22 mg/m ³ (worker systemic long term value)
		5.4 mg/m ³ (consumer systemic long term value)

CAS No.	Designation of material	%	Type	Value	Unit
CAS: 100-51-6 Benzyl alcohol					
AGW (Germany)	Long-term value: 22 mg/m ³ , 5 ppm				
	2(l);DFG, H, Y, 11				
HTP (Finland)	Long-term value: 45 mg/m ³ , 10 ppm				

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Use a moisturising skin cream after processing the product.

Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 4)

Protection of hands:

Protective gloves.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: \geq (Butyl) 0.7mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: $>$ 480 min

Value for the permeation: Level \leq 6

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Yellowish
Odour:	Amine-like
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point: Not applicable

Flammability (solid, gas): Not applicable.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Vapour pressure: Not determined.

Density at 20 °C: 1.0 g/cm³

Solubility in / Miscibility with

Water: Fully miscible

Segregation coefficient (n-octanol/water) log

Pow: Not determined.

Viscosity:

dynamic at 20 °C: 500 mPas

kinematic: Not determined.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 5)

Solvent separation test:	Not determined
Solvent content:	
EU-VOC (%)	2.00 %
9.2 Other information	None.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidizing agents

Exothermic polymerisation.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Poisonous gases/vapours

Corrosive gases/vapours

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 84144-79-6 N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether			
Oral	LD50	>300-1,000 mg/kg (Rat)	
CAS: 104-78-9 3-aminopropyldiethylamine			
Oral	LD50	1,410 mg/kg (Rat)	
Dermal	LD50	750 mg/kg (rbt)	
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,230 mg/kg (Rat)	
Dermal	LD50	2,000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
		>4,178 mg/l (Rat)	

Primary irritant effect:

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 6)

STOT-repeated exposure Based on available data, the classification criteria are not met.
Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Very toxic to aquatic life with long lasting effects.

Type of test Effective concentration Method Assessment	
CAS: 84144-79-6 N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether	
LC50/96h	0.66 mg/l (Fish)
EC50/48h	14 mg/l (Daphnia magna)
EC50/72h	0.17 mg/l (Algae)
CAS: 100-51-6 Benzyl alcohol	
LC50/48h	360 mg/l (Daphnia magna) 645 mg/l (Leuciscus idus (Orfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sunfish)) 460 mg/l (Pimephales promelas (Minnow))
EC50/24h	400 mg/l (Daphnia magna)
EC50/96h	400 mg/l (Daphnia magna) 640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

CAS: 100-51-6 Benzyl alcohol	
EBAB	1.1 log Pow (Bioaccumulation)

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark:

The product contains substances which are toxic to fishes and bacteria.
Very toxic for fish

Behaviour in sewage processing plants:

Type of test Effective concentration Method Assessment	
CAS: 100-51-6 Benzyl alcohol	
EC 50 (3h)	79 mg/l (Scenedesmus quadricauda (Algae))

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

12.6 Other adverse effects No further relevant information available.

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After mixing with the resin component pour a partial amount back into the curing agent barrel, stir well and pour the mass back once more. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN2735

14.2 UN proper shipping name
ADR

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-Propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated, N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether), ENVIRONMENTALLY HAZARDOUS

IMDG, IATA

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-Propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated, N-(2-Aminoethyl)-1,2-ethanediamine reaction products with glycidyl tolyl ether)

14.3 Transport hazard class(es)

ADR



Class

8 (C7) Corrosive substances.

(Contd. on page 9)

Safety Data Sheet
according to 1907/2006/EC, Article 31


Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 8)

Label	8
IMDG, IATA	
	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	
Hazard identification number (Kemler code):	Warning: Corrosive substances. 80
EMS Number:	F-A,S-B
Segregation groups	Alkalis
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
Not applicable.	
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2-PROPENENITRILE, REACTION PRODUCTS WITH ETHYLENEDIAMINE, HYDROGENATED, REACTION PRODUCTS WITH BENZALDEHYDE, DIETHYLENETRIAMINE AND TRIETHYLENETETRAMINE, HYDROGENATED, N-(2-AMINOETHYL)-1,2-ETHANEDIAMINE REACTION PRODUCTS WITH GLYCIDYL TOLYL ETHER), 8, III, ENVIRONMENTALLY HAZARDOUS

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Product safety department.

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 26.11.2020

Version number 4

Revision: 26.11.2020

Trade name weber.floor 4741 EP-Beschichtung SE Komp.B

(Contd. of page 10)

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG