

Fila Epox Waschhilfe

Epoxy Pro

Instant cleaner for fresh epoxy resin grout (RG)

Uses	Benefits
<ul style="list-style-type: none">• for removal of residues during cleaning of epoxy resin grouts• prevents the formation of matt edges• ideal for the cleaning of tools	<ul style="list-style-type: none">• no damage to aluminium and stainless steel profiles• without foaming• facilitates the washing of freshly grouted coverings with epoxy resin grouts

Fields of application

The ready-to-use cleaning aid simplifies the cleaning of fresh epoxy resin grouts on floors and walls; its Rapid Dry technology minimizes the formation of residual mortar hazes. Thanks to its thick-liquid consistency also wall surfaces can be treated by using a spray bottle. Furthermore ideal for the cleaning of tools. For use indoors and outdoors.

Description

Fila Epox Waschhilfe is an instant cleaner for fresh epoxy resin grouts.

Main features

- avoids residual hazes of epoxy mortar after cleaning
- prevents from matte marks
- ideal for cleaning of tools
- no detrimental effect on aluminium and stainless steel profiles
- ready-to-use
- bio-degradable
- high yield
- no foam formation
- for use indoors and outdoors

Technical values

Application temperature (air, substrate, material)	+5°C - +25°C
Composition	alkaline compound

Quality control

Fila Epox Waschhilfe is subject to a regular quality control.

General notes

- **Limits of use:** do not use **Fila Epox Waschhilfe** on absorbent surfaces, wood and metacrylate surfaces, and cured epoxy grouts.
-

Special notes

- During application wear safety goggles and gloves.
 - Always carry out a preliminary test on a trial area, in order to check the resistance of the product and the optimal waiting time for cleaning.
 - Do not let drip on surfaces which are not yet grouted.
 - Prior to use test the resistance of metal surfaces with the material.
-

Working instructions

Application

- The product is ready-to-use. Do not dilute it.
 - Pre-washing: use a white pad (type Scotchbrite®) and remove excess epoxy material on the grouted surfaces. Afterwards use a damp cellulose sponge (**weber.sys Fugenwaschschwamm**). Always soak the sponge in water and squeeze it before cleaning.
 - After-washing: spray **Fila Epox Waschhilfe** uniformly for the removal of all residues. Wait for 2 - 3 minutes. Again use the damp coarse-pore Spontex sponge without applying excessive pressure. Rinse frequently with water so as to keep the sponge clean.
 - If the final cleaning is to be done a few hours after completion of grouting works, leave the product in contact with the grouted surfaces for approx. 20 minutes.
 - Cleaning with **Fila Epox Waschhilfe** can be carried out up to a maximal delay of 24 hours after grouting.
 - If the cleaning has not taken place within the specified times, it is recommended to treat the cured epoxy residues with the specific cleaner **Fila CR10**.
-

Practical information

Colour:
light yellow

Tools:
white pad (type Scotchbrite®), cellulose sponge **weber.sys Fugenwaschschwamm**

Storage:
The product can be stored for at least 18 months in its original unopened packaging, if kept at temperatures between +5°C and +30°C.

Consumption/Yield

Large-size tiles	up to 350 meters and per operation
Mosaic	up to 15 m ² and per operation

Packagings

Type	Sales unit	Number
Plastic spray bottle (with trigger)	750 ml	12 bottles (cardboard)

The information in this technical data sheet is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.