

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weber.floor 4005

Safety data sheet no.: 49PM21256

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

e-mail: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number:

Emergency medical information in case of poisoning:

Poison Information Centre Mainz - Tel.: +49 (0) 6131 19240 (advice in German or English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 1)

H318 Causes serious eye damage.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P362 Take off contaminated clothing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	25-50%
CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO ₄ x n H ₂ O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	2-5%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	2-5%
CAS: 1332-58-7 EC number: 310-194-1	Kaolin substance with a Community workplace exposure limit	1-2%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 2)

After inhalation Supply fresh air; consult doctor in case of complaints.**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents**

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.**5.3 Advice for firefighters****Protective equipment:** Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.**6.3 Methods and material for containment and cleaning up:** Pick up mechanically.**6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

-EUG-

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 3)

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 65997-16-2 Cement, alumina, chemicals		
Inhalative	Derived No Effect Level	2.5 mg/m³ (worker systemic long term value) 5 mg/m³ (worker systemic short term value)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO4 x n H2O (n = 0; 1/2; 2)		
Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m³ (worker systemic long term value) 5,082 mg/m³ (worker systemic short term value) 5.29 mg/m³ (consumer systemic long term value) 3,811 mg/m³ (consumer systemic short term value)
CAS No. / Designation of material / % / Type / Value / Unit		
CAS: 14808-60-7 Silicon dioxide (Quartz sand)		
BOELV (European Union)	Long-term value: 0.1* mg/m³ *respirable fraction	
MAK (Germany)	Long-term value: 0.05 mg/m³ alveolengängige Fraktion	
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m³ Long-term value: 0.3* 0.1** mg/m³ *total; **total, respirabel: K	
LEP (Spain)	Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y	
TWA (Italy)	Long-term value: 0.025 mg/m³ A2, (j)	
VLE (Portugal)	Long-term value: 0.05 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão	
OEL (Sweden)	Long-term value: 0.1 mg/m³ C, M, respirabel fraktion	
HTP (Finland)	Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly	
CAS: 1317-65-3 calcium carbonate		
TWA (Italy)	Long-term value: 10 mg/m³ (e)	
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO4 x n H2O (n = 0; 1/2; 2)		
AGW (Germany)	Long-term value: 6 A mg/m³ DFG	

(Contd. on page 5)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 4)

LEP (Spain)	Long-term value: 10 mg/m ³ e
TWA (Italy)	Long-term value: 10 mg/m ³ (i)
VLE (Portugal)	Long-term value: 10 mg/m ³ Fração inalável; Sintomas nasais
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.; A4, função pulm., sintomas resp., asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae
CAS: 1332-58-7 Kaolin	
GV (Denmark)	Short-term value: 4 mg/m ³ Long-term value: 2 mg/m ³
LEP (Spain)	Long-term value: 2* mg/m ³ d, e *Fracción respirable
TWA (Italy)	Long-term value: 2 mg/m ³ A4 (e, j)
VLE (Portugal)	Long-term value: 2 mg/m ³ Fração resp.; A4; Pneumoconiose
HTP (Finland)	Long-term value: 2 mg/m ³ alveolijae

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Hand protection

Protective gloves.

(Contd. on page 6)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Recommended thickness of the material: ≥ 0.15 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level ≤ 6

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: According to product specification

Odour: Characteristic

Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower: Not determined.

Upper: Not determined.

Flash point: Not applicable

Auto-ignition temperature: Not determined.

Decomposition temperature: Not determined.

pH at 20 °C > 12.0 (DIN 19261)

Viscosity:

Kinematic viscosity Not applicable.

dynamic: Not applicable.

Solubility

Water at 20 °C: 1.5 g/l

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure: Not applicable.

Density and/or relative density

Density: Not applicable.

Bulk density: Not determined.

Vapour density Not applicable.

Particle characteristics

See section 3.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 6)

9.2 Other information	None.
Appearance:	
Form:	Powder
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Minimum ignition energy	
Solvent content:	
Organic solvents:	0.0 %
EU-VOC (%)	0.0000 %
EU-VOC (g/L)	0.0000 g/l
Solids content:	100.0 %
Change in condition	
Softening point/range	
Oxidising properties	Not determined.
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)

Trade name weber.floor 4005

10.6 Hazardous decomposition products: No dangerous decomposition products known. (Contd. of page 7)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 1317-65-3 calcium carbonate			
Oral	LD50	>5,000 mg/kg	(Rat)
CAS: 65997-16-2 Cement, alumina, chemicals			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test / Effective concentration / Method / Assessment	
CAS: 1317-65-3 calcium carbonate	
LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))
EC50/48h	>1,000 mg/l (Daphnia magna)
EC50/72h	>200 mg/l (Algae)
CAS: 65997-16-2 Cement, alumina, chemicals	
LC50/96h	100 mg/l (Fish)
EC50/48h	5.4 mg/l (Daphnia magna)

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 8)

EC50/72h	3.6 mg/l (Algae)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
LC50/48h	79-1,970 mg/l (Daphnia magna)
LC50/96h	>79 mg/l (Oryzias latipes (Japanese medaka))
	79-2,980 mg/l (Fish)
EC50/72h	>79 mg/l (Selenastrum capricornutum (Green algae))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

The product contains substances which causes severe clouding in water

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 65997-16-2 Cement, alumina, chemicals	
EC 50 (3h)	1,000 mg/l (Activated sludge)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
EC 50 (3h)	>1,000 mg/l (Activated sludge)

Remark: The product causes a significant pH change. Neutralise before introduction.

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

European waste catalogue	
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 10)

EUG

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 9)

Recommended cleaning agent:

Water, if necessary together with cleansing agents.
Thoroughly shake out sacks.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Not applicable.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

Not dangerous according to the above specifications.

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 11)

Trade name weber.floor 4005

(Contd. of page 10)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation	Expert judgement
Serious eye damage/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: Product safety department.

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Printing date 06.07.2023

Version number 1

Revision: 06.07.2023

Trade name weber.floor 4005

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

— EUG —