

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011
and Commission Delegated Regulation (EU) No 574/2014

No. DoP-DE-013913 001

1. *Unique identification code of the product type:*

013913 001 (weber.fug 883)
TYPE F – EXT-INT-CC according to EN 15651-1;
TYPE G-CC according to EN 15651-2;
TYPE S according to EN 15651-3

2. *Intended use/s:*

Sealant for facade for interior and exterior application, intended for use in cold climate.
Sealant used for sealing glazing applications, intended for use in cold climate.
Sealants used for sanitary applications.

3. *Manufacturer:*

Saint-Gobain Weber GmbH
Schanzenstr. 84
40549 Düsseldorf/Germany
<https://www.de.weber>

4. *Authorised representative:*

Not applicable

5. *System/s of AVCP:*

System 3: for essential characteristics
System 3: for reaction to fire

6. *Harmonised standard:*

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM
EN 15651-2:2012: Type G-CC: CLASS 25LM
EN 15651-3:2012: Type S: CLASS XS1

Notified body:

IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

7. Declared performance/s:

EN 15651-1:2012

Essential characteristics	Performance
Reaction to fire	Class E
Release dangerous chemicals	NPD
Water and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Elastic recovery	≥ 70%
Secant modulus at 23°C (N/mm ²)	≤ 0,4
Secant modulus at -20°C (N/mm ²)	≤ 0,6
Secant modulus at -30°C (N/mm ²)	≤ 0,9
Tensile properties at maintained extension	NF
Tensile properties at maintained extension at -30°C	NF
Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at maintained extension after water immersion	NF
Elongation at break	≥ 25%
Durability	Passed

Conditioning:

Method A

Test substrate:

Aluminium

Mortar

Declared performance/s:

EN 15651-2:2012

Essential characteristics	Performance
Reaction to fire	Class E
Release dangerous chemicals	NPD
Water and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Secant modulus at 23°C (N/mm ²)	≤ 0,4
Secant modulus at -20°C (N/mm ²)	≤ 0,6
Secant modulus at -30°C (N/mm ²)	≤ 0,9
Tensile properties at maintained extension at -30°C	NF
Tensile properties at maintained extension	NF
Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at maintained extension after water immersion	NF
Adhesion/cohesion after exposure to heat, water and artificial light	NF
Resistance to compression (N/mm ²)	0,26
Durability	Passed

Conditioning:

Method A

Test substrate:

Aluminium

Glass

Declared performance/s:

EN 15651-3:2012

Essential characteristics	Performance
Reaction to fire	Class E
Release dangerous chemicals	NPD
Water and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties at maintained extension	NF
Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at maintained extension after water immersion	NF
Microbiological growth	0
Durability	Passed


Conditioning:
Method A

Test substrate:
Aluminium
Glass

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Saint-Gobain Weber GmbH, Düsseldorf, 17.06.2024

ppa. 
ppa. Dr. Benjamin Krebs


i.V. Dirk Taron-Schreiber