

weber.therm 314

Fabric corner angle fine

PVC corner bracket with glued-on VWS fabric and fabric overhang at one end



Product profile

- To reinforce the corners
- For perpendicular and aligned edge formation

Product advantages

- Fabric 4 x 4 mm
- Reinforced with PVC profile

Product description

Perforated PVC angle with glued-on fibre Glass Mesh. The fabric overlap on one side enables optimum overlap between two profiles.

Product features

- Exact façade edge specified by PVC profile
- Optimum connection of the angle to the reinforcement thanks to the glass fibre fabric
- Very good connection to the foundation masonry due to perforated profile design
- No cracking
- Simple application

Technical values

Profile length	2.5 m
Fabric width left/right	10 cm x 15 cm / 10 cm x 23 cm
Fabric type and fabric width	160 g, 25 cm red / 160 g, 33 cm red
Fabric print	weber + logo
Content/pallet	5250 linear metres/pallet
Profile material	Polyvinyl chloride (PVC)
Fabric material	fibre Glass Mesh

Application

Surface preparation

Application

Cut the profile to the required length using suitable support shears. The angle must be fully embedded in the underlay/armour plaster at all corners and edges. For window corners, cut the side length to match the reveal depth. The surface reinforcement with fabric is then led up to the plaster edge and embedded.

weber.therm 314

Fabric corner angle fine

Packaging units

Type	Pack size	PU
rods	2.50 meter	50 rods / box

The information in this technical information is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.

Registered office: Schanzenstr. 84 | 40549 Düsseldorf
Contact: export.de.weber@saint-gobain.com | www.de.weber
Commercial register: AG Düsseldorf HRB 65250 | VAT no.: DE 122392875