

weber.prim 403

Universal primer

Organic, solvent-free, white-pigmented primer coat for equalizing porosity of substrates and for improving adhesion



Product profile

- for indoor and outdoor use
- wall, ceiling
- new construction, renovation

Product advantages

- reduces the porosity of the whole substrate
- primer for thin-layer finish top coats

Product description

weber.prim 403 is a factory-produced, organic, white-coloured primer.

Fields of application

weber.prim 403 is used for levelling compounds on uneven substrates with different absorbency and for improving adhesion.
weber.prim 403 is a primer for thin-layer finish top coats.

Product features

- reduces the porosity of the whole substrate
- primer for thin-layer finish top coats
- available as a tinted version (15-litre bucket)
- drying time: approx. 24 hours
- solvent-free

Consumption / yield

depending on substrate	approx. 0.25 l/m ²
depending on substrate	approx. 20.0 m ² /5 l
depending on substrate	approx. 60.0 m ² /15 litres

Technical values

Base color	white colored
Composition	organic binders, alkali-resistant colour pigments, fine sands

Storage

Shelf life	min. 12 months
Storage conditions	In the original unopened packaging, frost-free and away from direct sunlight (at temperatures between + 5 to + 30 °C).

weber.prim 403

Universal primer

Application

Surface preparation

- The substrate must be load-bearing, dry and clean.
- Dirt, dust and loose parts must be removed from the surface.

Application

- The primer can be applied with a roller or paint brush.
- Applying too much primer can lead to film formation (gloss), which can cause adhesion problems with the product applied afterwards.

General notes

Do not add any foreign substances to the primer.

The temperature of the air, materials used and substrate must be at least +5°C during application and drying.

Consumption may vary depending on the surface type and application method. Exact consumption values must be determined by testing different areas of the object.

weber.prim 403 is subject to regular quality control through self-monitoring

Packaging units

Type	Unit	PU
bucket	5 litre	60 buckets / palett

The information in this technical information is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.

Registered office: maxit west GmbH | Paul-Mathis-Str. 1 | 79291 Merdingen
Contact: info@weber-maxit.de | www.weber-maxit.de
Commercial register: AG Freiburg im Breisgau HRB 733505 | VAT no.: DE455990071

Version: 2025-10-07 | page: 2/2