

## weber.prim 405

Insulating primer

Organic, solvent-free, white-pigmented primer for evening out unevenly absorbent substrates

### Product profile

---

- for indoor and outdoor use
- wall, ceiling
- new construction, renovation

### Product advantages

---

- reduces the porosity of the whole substrate
- vapour permeable
- alkali-resistant

### Product description

---

**weber.prim 405** is a factory-produced, organic, white-pigmented primer.

### Fields of application

---

**weber.prim 405** is used for evening out unevenly absorbent substrates. **weber.prim 405** evens out the absorbency of a variety of surfaces, preventing the water in the subsequent render coat from being absorbed too quickly.

### Product features

---

- reduces the porosity of substrates
- is vapour permeable
- alkali-resistant
- drying time: is approx. 12 hours
- solvent-free

### Consumption / yield

---

depending on substrate

approx. 0.2 l/m<sup>2</sup>

### Technical values

---

Base color

white colored

Composition

organic binders, alkali-resistant colour pigments

### Storage

---

Shelf life

min. 12 months

Storage conditions

In the original unopened packaging, frost-free and away from direct sunlight (at temperatures between + 5 to + 30 °C).

### Application

---

#### Surface preparation

- The surface must be load-bearing, dry and clean.
- Dirt, dust and loose parts must be removed from the surface.

## weber.prim 405

Insulating primer

### Application

- Can be applied with a roller, ceiling brush or suitable spraying equipment.
- Applying too much can lead to film formation (gloss) and thus to adhesion problems for the subsequent coating.
- The temperature of the air and the substrate during application must not be below + 5 °C.

### General notes

---

**weber.prim 405** is subject to regular quality control through self-monitoring.

### Packaging units

---

Type	Unit	PU
bucket	15 litre	24 buckets / palett

The information in this technical information is based on our current knowledge and experience at the time of printing. However, they do not guarantee in the legal sense.

Registered office: maxit west GmbH | Paul-Mathis-Str. 1 | 79291 Merdingen  
Contact: [info@weber-maxit.de](mailto:info@weber-maxit.de) | [www.weber-maxit.de](http://www.weber-maxit.de)  
Commercial register: AG Freiburg im Breisgau HRB 733505 | VAT no.: DE455990071